D&LLTechnologies



PowerEdge R760xs

Best choice in balanced compute and flexible storage for the most popular IT application

Buy the performance and flexibility you need

The new Dell PowerEdge R760xs is a 2U, two-socket rack server. Buy the best fit in scalable performance and large storage capability with this purpose-built 2U system. Focused on delivering the latest technology to power the most popular applications and workloads used by businesses today, including virtual desktop infrastructure (VDI), virtual machines (VMs), and software-defined storage (SDS). All delivered in a thoughtfully crafted platform that will provide balanced compute that fits in your current infrastructure.

Easily configurable

- Add up to two 5th generation Intel® Xeon® Scalable processors with up to 28 cores and 4th generation Intel® Xeon® Scalable processors with up to 32 cores per socket for faster performance
- Accelerate in-memory workloads with up to 16 DDR5 RDIMMS up to 5200 MT/sec
- Improve data throughput and reduce latency with support up to 8 I/O device (up to available 6 PCIe slots, 1 OCP 3.0 networking slot, and 1 dedicated PERC slot)
- Storage options include up to 12x 3.5" HDDs/SSDs, or up to 16x 2.5" HDD/SSDs, plus up to 8x NVMe drives

A breeze to cool

- · Thoughtfully designed to fit in your current air-cooled infrastructure
- · Alleviate the worry about expensive liquid cooling retrofitting to your data center
- · Synchronize your workload needs with a tailored performance configuration that is air cooled
- Minimize the carbon footprint of your data center by better matching the system power consumption with anticipated workload requirements

Cyber Resilient Architecture for Zero Trust IT environment & operations

Security is integrated into every phase of the PowerEdge lifecycle, including protected supply chain and factory-to-site integrity assurance. Silicon-based root of trust anchors end-to-end boot resilience while Multi-Factor Authentication (MFA) and role-based access controls ensure trusted operations.

Increase efficiency and accelerate operations with autonomous collaboration

The Dell OpenManage[™] systems management portfolio delivers a secure, efficient, and comprehensive solution for PowerEdge servers. Simplify, automate and centralize one-to-many management with the OpenManage Enterprise console and iDRAC.

Sustainability

From recycled materials in our products and packaging, to thoughtful, innovative options for energy efficiency, the PowerEdge portfolio is designed to make, deliver, and recycle products to help reduce the carbon footprint and lower your operation costs. We even make it easy to retire legacy systems responsibly with Dell Technologies Services.

Rest easier with Dell Technologies Services

Maximize your PowerEdge Servers with comprehensive services ranging from Consulting, to ProDeploy and ProSupport suites, Data Migration and more – available across 170 locations and backed by our 60K+employees and partners.

PowerEdge R760xs

The Dell PowerEdge R760xs offers compelling performance in a right-sized system with the latest PCIe Gen 5 bandwidth and large storage capability to support:

- Virtual Desktop Infrastructure (VDI)
- Virtual Machines (VMs)
- Software-Defined Storage Node

Feature	Technical Specifications	
Processor	Up to two 5th Generation Intel Xeon Scalable processor with up to 28 cores and 4th Generation Intel Xeon Scalable processor with up to 32 cores per processor	
Memory	 16 DDR5 DIMM slots, supports RDIMM 1.5 TB max, speeds up to 5200 MT/s, supports registered ECC DDR5 DIMMs only 	
Storage	Internal Controllers: PERC H965i, PERC H755, PERC H755N, PERC H355, HBA355i, HBA465i	
controllers	 Internal Boot: Boot Optimized Storage Subsystem (BOSS-N1): HWRAID 1, 2 x M.2 NVMe SSDs or USB External HBA (non-RAID): HBA355e; Software RAID: S160 	
GPU Options	2 x 75 W SW, LP	
Drive Bays	Front bays:	Rear bays:
	 0 drive bay Up to 8 x 3.5-inch SAS/SATA (HDD/SSD) max 192 TB Up to 12 x 3.5-inch SAS/SATA (HDD/SSD) max 288 TB Up to 8 x 2.5-inch SAS/SATA/NVMe (HDD/SSD) max 122.88 TB Up to 16 x 2.5-inch SAS/SATA (HDD/SSD) max 121.6 TB Up to 16 x 2.5-inch (SAS/SATA) + 8 x 2.5-inch (NVMe) (HDD/SSD) max 244.48 TB 	 Up to 2 x 2.5-inch SAS/SATA/NVMe (HDD/SSD) max 30.72 TB (supported only with 12 x 3.5-inch SAS/SATA HDD/SSD configuration)
Hot swap	• 1800 W Titanium 200—240 VAC or 240 VDC	 1100 W -(48V — 60V) DC
Redundant Power	• 1400 W Titanium 100—240 VAC or 240 VDC	• 800 W Platinum 100—240 VAC or 240 VDC
Supplies	 1400 W Platinum 100—240 VAC or 240 VDC 	• 700 W Titanium 200—240 VAC or 240 VDC
	1400 W Titanium 277 VAC or HVDC (HVDC stands for High-	600 W Platinum 100—240 VAC or 240 VDC
	Voltage DC, with 336V DC)	
	• 1100 W Titanium 100-240 VAC or 240 VDC	
Cooling Options	Air cooling	
Fans	• Standard (STD) fans/High performance Silver (HPR) fans/ High performance Gold (VHP) fans, Up to 6 hot swappable fans	
Dimensions and	 Height – 86.8 mm (3.41 inches) 	 Depth – 707.78 mm (27.85 inches) – without bezel
Weight	 Width – 482 mm (18.97 inches) 	721.62 mm (28.4 inches) – with bezel
		 Weight – Max 28.6 kg (63.0 lbs.)
Form Factor	2U rack server
Embedded	iDRAC9	iDRAC Service Module
Management	iDRAC Direct	Quick Sync 2 wireless module
	iDRAC RESTful API with Redfish	
Bezel	Optional LCD bezel or security bezel	
OpenManage	 CloudIQ for PowerEdge plug in 	 OpenManage Integration with Windows Admin Center
Software	OpenManage Enterprise	OpenManage Power Manager plugin
	OpenManage Enterprise Integration for VMware vCenter	OpenManage Service plugin
	OpenManage Integration for Microsoft System Center	OpenManage Update Manager plugin
Mobility	OpenManage Mobile	
OpenManage	BMC Truesight	Red Hat Ansible Modules
Integrations	Microsoft System Center	Terraform Providers
	 OpenManage Integration with ServiceNow 	 VMware vCenter and vRealize Operations Manager
Security	Cryptographically signed firmware	 Secured Component Verification (Hardware integrity check)
	Data at Rest Encryption (SEDs with local or external key mgmt)	Silicon Root of Trust
	Secure Boot	 System Lockdown (requires iDRAC9 Enterprise or Datacenter)
	Secure Erase	TPM 2.0 FIPS, CC-TCG certified, TPM 2.0 China NationZ
Embedded NIC	2 x 1 GbE LOM	
Network options	1 x OCP card 3.0 (optional)	
Ports	Front Ports:	Rear Ports
	 1 x iDRAC Direct (Micro-AB USB) port, 1 x USB 2.0, 1 x VGA 	 1 x Dedicated iDRAC Ethernet port, 1 x USB 2.0, 1 x USB 3.0,
	Internal Ports: 1 x USB 3.0 (optional)	1 x VGA, 1 x Serial (optional)
PCle	1 CPU Configuration: Up to 4 PCIe slots (2 x8 Gen5, 1 x16 Gen4, 1 x8 Gen4)	
Operating System	• 2 CPU configuration: Up to 6 PCIe slots (2 x16 Gen5, 3 x16 Gen4, 1 x8 Gen4) • Microsoft Windows Server with Hyper-V • VMware ESXi	
Operating System and Hypervisors		
	Red Hat Enterprise Linux	Canonical Ubuntu Server LTS
	SUSE Linux Enterprise Server	For specifications and interoperability details, see Dell.com/OSsupport.
OEM-ready version available	Solutions -> OEM Solutions.	they were designed and built by you. For more information, visit Dell.com ->

APEX Flex on Demand

Acquire the technology you need to support your changing business with payments that scale to match actual usage. For more information, visit https://www.delltechnologies.com/en-us/payment-solutions/flexible-consumption/flex-on-demand.htm.

Discover more about PowerEdge servers



Learn more about our

PowerEdge servers



Learn more about our systems management solutions



Search our Resource Library







Contact a Dell Technologies Expert for Sales or Support

Copyright © 2024 Dell Inc. or its subsidiaries. All Rights Reserved. Dell Technologies, Dell, and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be trademarks of their respective owners.

